



Spectator Rail 1.2m high

Lineposts at 2.525m centres to be either 70x70mm or 60x40mm rectangular hollow section steel

Top rail - 48.3mm or 42mm circular hollow section fitted into the posts with concealed internal fittings

200x50mm galvanised or galvanised and polyester powder coated twin 8mm diameter horizontal wires sandwiching single 6mm diameter vertical wires, standard panel width of 2.515m for a 2.525m standard post centre

Welded mesh is erected to posts in two lifts from panels, typically 2m each fitted into brackets on the face of posts, U shape brackets secured to the face of the posts at 400mm centres, face of posts complete with neoprene blend strip set between post/bracket and the panels to provide noise reduction, all supported on the rhs lineposts set in concrete at maximum 2.525m centres (as per detail)

Addl end or corner posts same dimensions as lineposts

Single leaf gate typically 1.2m wide between posts x 2m high + lintel panel over to 3m, gate end posts typically 80x80mm rhs or 100x100mm rhs

Double leaf gate typically 3m wide between posts x 2.5m high + lintel panel over to 3m, gate end posts typically 80x80mm rhs or 100x100mm rhs

**JB Corrie & Co. Limited**  
*Fencing Contractors & Manufacturers*



Frenchmans Road  
 Petersfield  
 Hants  
 GU32 3AP  
 Email: [fencing@jbcorrie.co.uk](mailto:fencing@jbcorrie.co.uk)

Tel: 01730 237100  
 Fax: 01730 264915  
 Web: [www.jbcorrie.co.uk](http://www.jbcorrie.co.uk)

JBC Ref.: JB Corrie	
JB Corrie : JB Corrie	
Drg. no.: JBC_specrailCP_126	
Scale: Not to Scale	Paper Size: A4
Drawn by & date:	Reviewed by & date:
LR	LR - 17.02.09

Description: 1.2m spectator rail corrieplay standard infill	
Site: not known	
Revision history:	Notes: 1. All dimensions in mm unless otherwise indicated.